

Smart Dongle



Smart

2G, 3G, 4G / WLAN communication ¹
Support 3rd-party monitoring system ²



Simple

Plug & Play



Reliable

IP65
Support auto reconnection

Technical Specification

Smart Dongle-WLAN

Smart Dongle-4G

General Data

Connection interface	USB
Installation	Plug-and-play
Indicator	LED Indicator
Dimensions (W x H x D)	130 x 48 x 33 mm (5.1 x 1.9 x 1.3 inch)
Weight	90 g (0.2 lb.)
Degree of protection	IP65
Power consumption (typical)	2 W
	3.5 W

Wireless Parameter

Sim card type	/	mini-sim (15 mm x 25 mm)
Supported standards & frequencies	802.11 b / g / n 2.4 GHz	4G: FDD-LTE / TDD-LTE 3G: WCDMA / HSDPA / HSUPA / HSPA+ 2G: GSM / GPRS / EDGE ³

Environment

Operating temperature range	-30 °C ~ +65 °C (-22 °F ~ 149 °F)
Relative humidity range	5 - 95% RH
Storage temperature range	-40°C ~ +70°C (-40 °F ~ 158 °F)
Max. operating altitude	4,000 m (13,123 ft.)

Standard Compliance (more available upon request)

Certificate	CE, RCM	CE, Type Approval for Thailand
-------------	---------	--------------------------------

Inverter Compatibility

Inverter model	SUN2000-3/4/5/6/8/10KTL-M0 Sun2000-12/15/17/20KTL-M0	SUN2000-3/4/5/6/8/10KTL-M0 Sun2000-12/15/17/20KTL-M0 SUN2000-60KTL-M0
----------------	---	---

¹ To ensure stable data transmission, Huawei suggests 4G dongle be installed in areas with stable mobile signal (2G signal ≥4 bars, 3G/4G signal ≥3 bars).

² 3rd-party management system shall match the communication protocol with Huawei Smart Dongle.

³ For recommended carriers list and details on supported frequencies, please contact local distributors